

SPECIFICATION SHEET: **SYSTEM 1300 VEDETTE RANGE** **WELLED (1307) – DIVIDED (1308) – UNIFORM (1309)**

Please refer to Specification Sheet: S001 for general specification, material and construction.



Divided (1308):

Dimensions:

Height	Width	Depth	Nest
1775 mm	300 mm	300 mm	1 2 3
1775 mm	300 mm	450 mm	1 2 3
1775 mm	300 mm	550 mm	1 2 3
1775 mm	380 mm	380 mm	1 2 3
1775 mm	380 mm	450 mm	1 2 3
1775 mm	380 mm	550 mm	1 2 3
1775 mm	450 mm	450 mm	1 2 3
1775 mm	450 mm	550 mm	1 2 -

With addition of a specially designed steel sheet divider, fitted below the shelf, the VEDETTE locker can be converted into this multi-purpose model; the divider separating soiled clothing from other clean garments. All other details as for the VEDETTE Full Length range.

Welled (1307):

Dimensions:

Height	Width	Depth	Nest
1775 mm	380 mm	450 mm	1 2 -

This locker has been designed with a foreshortened door to be used in conjunction with an integral stand with seat. The seat slat is manufactured from hardwood, postformed profile and finished with two coats of clear lacquer and is 382 mm high overall. Underside of seat to floor is a nominal 337 mm. All legs fitted with adjustable feet giving approximately 30 mm of adjustment. At the bottom of the 'well' a 20 mm gap is provided for easy cleaning of the unit.

Uniform (1309):

Dimensions:

Height	Width	Depth	Nest
1775 mm	450 mm	450 mm	1 2 -

By adapting the 450 mm square DIVIDED locker with three fixed shelves, useful storage compartments are achieved.

The compartments, which are situated on the lock clip side of the unit under the shelf, are of the following dimensions:

- 280 mm high x 225 mm wide x 450 mm deep
- 280 mm high x 225 mm wide x 450 mm deep
- 280 mm high x 225 mm wide x 450 mm deep
- 535 mm high x 225 mm wide x 450 mm deep

All other details as for the VEDETTE Full Length range.

Strength and Security with Style

- Sturdy Construction: Door frame constructed from heavy gauge mild steel of press formed channel section.
- Door Strength: Full length door stiffeners for extra door rigidity and three 'five knuckle' semi-concealed hinges.
- Style: Attractive and functional locker design.
- Colour: Automated paint plant ensures consistent high quality finish in a wide range of modern colours.

Detailed Product Specification

- Nesting: Lockers can be supplied as single units or nested in groups during the manufacturing process. All lockers are holed in back and sides to enable them to be bolted together into rows or back to back to suit your requirements. **Note:** When preparing locker room layouts allow approximately 4 mm extra for each nest for rivet heads at the sides of lockers in each row.
- Construction: Spot welded and pop riveted.
- Material: Mild steel Powder Coated.

	76.6	Xh	
--	------	----	--

- Door Frame Assembly:** Comprising two uprights manufactured from heavy gauge mild steel of press formed channel section; top and bottom cross members which are designed to create door stops. Spot welded construction produces a rigid frame enabling door clearances to be maintained in accordance with British Standard requirements. The top cross member is provided with a series of ventilation slots.
- Doors:** Doors are attached to the right hand side of door frame upright with three 'five knuckle' semi-concealed hinges. Doors are fitted with a plastic escutcheon plate around the lock, which can also act as a name card/locker number holder. The inside of the door has a full length vertical 'stiffener' to provide greater rigidity. Two rubber buffers are fitted to the top and bottom corners of the door for quiet closure.
- Bottom:** The bottom is formed as a 60 mm high plinth. All edges have return bends and the front and rear edges drilled for fitting to stands or stands with seat.
- Shelf:** The lockers are fitted with a shelf 315 mm from the top, giving a clear 250 mm opening, allowing adequate space for the average crash helmet with chin protector, or other articles.
- Hook & Hanger Rails:** A coat hook is located each side of the main compartment under the shelf; for lockers over 300 mm deep a plastic coated clothes hanger rail is also fitted.
- Locking:** Standard options are either 10 disc tumbler cam lock in mastered suite with two keys to each lock or, at no extra cost, a latch lock for the user's own padlock (recommended padlock shank dimensions 6 mm).
As an optional extra for added security we can supply full reach espagnolette bolts giving three point locking (ie, top, bottom and centre) with either of the standard locking options. We can also supply, as an optional extras, a wide range of locking options, please ask for details.
- Ventilation:** Ventilation is provided by a series of unique ventilation slots in the top cross member.
- Paint Finish:** Five stage automatic degreasing and phosphating process to remove surface contamination. This base gives improved adhesion and humidity resistance. The powder is electrostatically applied prior to oven baking at the appropriate temperature.
- Colour Range:** Standard locker frame Powder Coated colours is: "Ice". Standard door colours are: "Ice", "Black", "Rockpool", "Smoke", "White", "Skye", "Yellow", "Royale", "Forest" and "Cherry". Exact colour samples are available.
- OPTIONAL EXTRAS:** The following can be supplied at an additional cost and, if included, will be specified in the quotation.
- Three Point Locking:** The system provides effective and secure latching, allowing locking at three positions.
- Perforation:** Where Full Length Lockers have perforated doors it is strongly recommended that three point locking be fitted for added security.
- Locker Numbering:**
- Number Label – Made of silver polyester, with a permanent, self-adhesive back. Numbers are printed in black and can comprise one to four digits including letters.
 - Number Plate – Made of laminated plastic, white numbers on black, numbers can comprise one to four digits.
 - Number Discs – Laminated plastic 25 mm diameter, white numbers on black, numbers can comprise one to four digits. The disc is holed and a split key ring is provided.
- Stands/with Seats:** Lockers can be provided with either stands or stands with seats, with or without adjustable feet. Please refer to Specification Sheet S015.
- Sloping Tops:** Lockers can be manufactured with a sloping top. Gradient 1:3, ie
300 mm deep unit increased height at rear 100 mm
380 mm deep unit increased height at rear 126 mm
450 mm deep unit increased height at rear 150 mm
- End Panels:** For aesthetic appearance and to protect row ends, specifically designed end panels are available.
- Installation:** We can offer a full installation service for all lockers.

- **Health & Safety: Lockers must be firmly secured to wall or floor and fixed together in runs for safety purposes. If applicable, install in accordance with specific product instructions.**
- **All dimensions are nominal.**
- **To enable us to interpret your requirements accurately, please state at time of enquiry/order the choice of locker type, colour, locking and nesting arrangement and delivery requirement.**
- **The products described in this specification sheet herein are the subjects of patent, trademark, design and copyright protection or application thereof.**
- **In the interest of efficiency and service to our customers, the company reserves the right to modify the specifications of any of its products.**



Email: info@workarealtd.com

Website: www.workarealtd.com

Like us on Facebook



Follow us on Twitter