



|      |    |  |  |
|------|----|--|--|
| 76.6 | kh |  |  |
|------|----|--|--|

## ***SPECIFICATION SHEET: SYSTEM 1900D, GARMENT DISPENSER***



|                         |               |              |              |
|-------------------------|---------------|--------------|--------------|
| <b>Sizes available:</b> | <b>Height</b> | <b>Width</b> | <b>Depth</b> |
|                         | 1820 mm       | 380 mm       | 450 mm       |

### **Nominal size of individual compartments:**

|                | <b>Height</b> | <b>Width</b> | <b>Depth</b> |
|----------------|---------------|--------------|--------------|
| 5 Compartment  | 322 mm        | 380 mm       | 450 mm       |
| 8 Compartment  | 195 mm        | 380 mm       | 450 mm       |
| 10 Compartment | 156 mm        | 380 mm       | 450 mm       |
| 15 Compartment | 100 mm        | 380 mm       | 450 mm       |
| 20 Compartment | 71 mm         | 380 mm       | 450 mm       |

### ***Strength and Security with Style***

|                     |   |
|---------------------|---|
| Sturdy Construction | Door frame constructed from heavy gauge mild steel of press formed channel section.             |
| Door Strength       | Main outer frame supported by full length hinge.  |
| Door Security       | All compartments fitted with 10 disc, tumbler cam lock.   |
| Style               | Attractive and functional locker design.  |
| Colour              | Automated paint plant ensures consistent high quality finish in a wide range of modern colours. |

### ***Detailed Product Specification***

|                      |   |
|----------------------|---|
| Nesting:             | All Garment Dispensers are drilled to enable bolting together or to Garment Collectors to suit your requirements.   |
| Construction:        | Spot welded and pop riveted.  |
| Material & Finish:   | Mild steel-Powder Coated.   |
| Door Frame Assembly: | This comprises an inner and outer door frame. The outer frame is manufactured from heavy gauge mild steel channel section. The inner frame is fabricated from heavy gauge mild steel channel with tubular cross members. The inner frame is hinged by means of a full length hinge rod 8 mm diameter manufactured from galvanised mild steel. |
| Doors:               | The small compartment doors are hinged by means of the full length hinge rod. Each door has a rubber buffer to prevent opening damage.  |
| Numbering:           | Both inside and outside of the doors can be numbered with thermographic number labels for easy compartment identification.  |
| Bottom:              | The bottom is formed as a 50 mm high inverted plinth with return bends at the bottom edge. Edges holed at sides for fitting to stands.  |
| Internal Shelves:    | All shelves have safety over and flat front edges.  |
| Locking:             | The inner door is secured by a 10 disc tumbler cam lock. All small compartments are fitted with 10 disc tumbler cam locks with two keys to each lock. On delivery of units the keys are fixed to each internal compartment shelf for easy compartment identification.   |
| Paint Finish:        | Five stage automatic degreasing and phosphating process to remove surface contamination. This base gives improved adhesion and humidity resistance. The powder is electrostatically applied prior to oven baking at the appropriate temperature.  |

|      |    |  |  |
|------|----|--|--|
| 76.6 | kh |  |  |
|------|----|--|--|

Colour Range: Standard locker frame Powder Coated colours is: "Ice". Standard door colours are: "Ice", "Black", "Rockpool", "Smoke", "White", "Skye", "Yellow", "Royale", "Forest" and "Cherry". Exact colour samples are available.

**OPTIONAL EXTRAS:** The following can be supplied at an additional cost and, if included, will be specified in the quotation.

Stands: Garment Dispensers can be provided with stands giving 150 mm clearance. Adjustable feet can also be provided.

Sloping Tops: Garment Dispensers can be manufactured with a 150 mm sloping top.

Three Point Locking: The system increases the security of the main door by providing locking in three positions.

End Panels: For aesthetic appearance and to protect row ends, specifically designed end panels are available.

Installation: We offer a full installation service for its products.

- **Health & Safety: Lockers must be firmly secured to wall or floor and fixed together in runs for safety purposes. If applicable, install in accordance with specific product instructions.**
- **All dimensions are nominal.**
- **To enable us to interpret your requirements accurately, please state at time of enquiry/order the choice of locker type, colour, locking and nesting arrangement and delivery requirement.**
- **The products described in this specification sheet herein are the subjects of patent, trademark, design and copyright protection or application thereof.**
- **In the interest of efficiency and service to our customers, the company reserves the right to modify the specifications of any of its products.**



Email: [info@workarealtd.com](mailto:info@workarealtd.com)

Website: [www.workarealtd.com](http://www.workarealtd.com)

**Like us on Facebook**



**Follow us on Twitter**